

The Turnstile Factory

BEACON SERIES OPTICAL TURNSTILES AND ADA GATES

Beacon Series™, Models BE-800-X (Subject to change without notice.)

CABINET-STYLE, WAIST-HIGH OPTICAL TURNSTILES

TURNSTILE SPECIFICATION: SECTION 10450

1.00 PART I GENERAL

- 1.01 Drawings and general provisions as specified apply to this section.**
- 1.02 Product Data - Manufacturer's general description for each item and related components. For specific information, see catalog.**
- 1.03 Shop drawings submitted upon request.**
- 1.04 The Controlled Access, Inc. Optical Turnstiles will utilize the building access control systems to grant or deny access.**
- 1.05 High-speed/nonrestrictive pedestrian passageways. Passageways are truly bi-directional at all times.**

2.00 PART II PRODUCTS

2.01 Turnstile models as manufactured by The Turnstile Factory, Hinckley, Ohio

2.02 BEACON™ SERIES

- 202.1 Bollard construction: 304 Stainless steel. No. 4 brushed satin finish. Dimensions: 27-1/4" long x 37" high x 8-7/8" wide.**
- 202.2 Top surface: 304 Stainless steel. No. 4 satin finish.**
- 202.3 Optical sensors provide for passage for up to 30 people per minute. Throughput is dependent on type of card reader technology and response time of the access system.**
- 202.4 Visual and audible annunciation is provided at each passageway to provide status of passageway, indication of valid card read, or alarm condition.**
- 202.5 Horizontal Graphic Arrays/HGA's/solid state.**
- 202.6 Optical sensors are provided to prevent individuals from obtaining unauthorized access by crawling through the lane.**
- 202.7 Distinctive tones for valid card and alarm condition. Adjustable volume control with an 82 db maximum. Buzzer sounds upon alarm condition.**
- 202.8 All components are designed specifically by Controlled Access, Inc. for optical turnstile pedestrian control products, and made in the USA.**
- 202.9 All components including the HGA's are solid state in design and are virtually maintenance free.**
- 202.10 Power requirements: Power supply input 100/120/220/230/240 VAC 50/60HZ Output - 24 VDC @ 2 amps. per passageway.**

2.03 OPTIONS

- 203.1 Optional console device can remotely monitor and control lane use.**
- 203.2 Alarm outputs: N/C, N/O relay rated at 5 amp @24 VDC/auxiliary alarm output contacts provided for interface to building access control, fire/life safety, security, CCTV and monitoring systems.**

3.0 PART III EXECUTION

3.01 Purchaser to install units in accordance with manufacturer's shop drawings and installation manual.

3.02 Warranty: Units are warranted against defects in materials and workmanship for a period of two years from date of delivery. See Warranty information for specific details.